



# DIMENSION™



## FABRICS

Cotton, Uncoated Polyester, Cotton/Poly blends, Polyester/Acrylic - **Excluding** Nylon and Dazzle Cloth

## SIZING

Available Widths (in.): 19.5" only  
Available Lengths (ft.): 10', 20', and 30' rolls

## THICKNESS

24 mils/600 microns



### SPECIAL PRECAUTIONS

Will NOT stretch. We do not recommend cutting fine, detailed designs with this product.



Use to create 3-dimensional designs.  
Very thick and durable.  
Free from PVC, plasticizers, & heavy metals.  
Manufactured without a sticky carrier for easy stacking of weeded designs.



White  
DIM-001



Black  
DIM-002

### MIRRORING

Cut this material into a mirror image.



### CUTTING

60° Blade Recommended, with high pressure - may need to cut twice.



### TEMPERATURE

320°F



### PRESSING | TIMING

Medium pressure | 25 seconds



### PEELING

Peel cold



### WASHING

Wash inside-out, warm water, and hang to dry. **NOT** suitable for dry-cleaning or tumble drying.



### LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.



**"It's best to test!"** Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing the material. Dye migration may occur with low-energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability whatsoever in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under the manufacturer's control and is not responsible for issues due to third-party material qualities. The Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.

©2023 Specialty Materials & Digital Decoration, LLC. | A POLI-TAPE Company | All rights reserved | Tulsa, OK 74146 | 877-437-8556

Tech Help: [tech@specialtymaterials.com](mailto:tech@specialtymaterials.com) | Sample Request: [samples@specialtymaterials.com](mailto:samples@specialtymaterials.com)