



DecoFILM® Paint FX



FABRICS

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Wool, Linen - **Excluding Nylon**

SIZING

Available Widths (in.): 15" and 20"
Available Lengths (ft.): 15', 30', 45', 60', and 90' rolls

THICKNESS

4 mils/100 microns

Pearlescent transfer films that resemble the shimmer of new car paint. Easy to cut and weed. It can be used on sports and leisure wear. Pressure-sensitive carrier enables easy weeding and repositioning.



COLOR VARIATION

During manufacturing, color variation can occur between rolls. This is especially true for Neon colors.



MIRRORING

Cut this material into a mirror image.



CUTTING

45° Blade Recommended



TEMPERATURE

310°F-330°F



PRESSING | TIMING

Firm pressure | 17-20 seconds



PEELING | RE-PRESS

Peel warm, cover with a PTFE sheet, and re-press for 2 seconds.



WASHING

Wash inside out cold water, gentle cycle. Dry low heat. Suitable for dry-cleaning.



LASER COMPATIBLE

This product contains no PVC and will not emit hazardous fumes.



"It's best to test!" Pre-test on an inconspicuous area before applying final production. Some garments require pre-heating and treatment, such as blotting moisture-wicking material with rubbing alcohol, before pressing the material. Dye migration may occur with low-energy dyes in polyester and blend fabrics. Check for compatibility and pre-treatment suggestions with each product's instructions. The user assumes all risk and liability whatsoever in connection with the use of this product. Specialty Materials cannot guarantee performance for conditions not under the manufacturer's control and is not responsible for issues due to third-party material qualities. The Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by the manufacturer.

©2023 Specialty Materials & Digital Decoration, LLC. | A POLI-TAPE Company | All rights reserved | Tulsa, OK 74146 | 877-437-8556

Tech Help: tech@specialtymaterials.com | Sample Request: samples@specialtymaterials.com

